

SAFETY DATA SHEET

111101-001 - NowoMetal - Roof Top WB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

111101-001 - NowoMetal - Roof Top WB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint for metal surfaces

Restricted to professional users.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

NOWOCOAT INDUSTRIAL A/S

Stålvej 3

6000 Kolding

Denmark

Tel: +45 7550 1111

E-mail

mail@nowocoat.dk

Revision

10/10/2025

SDS Version

7.0

Date of previous version

30/09/2025 (6.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 111 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

Not applicable.

Prevention

Not applicable.

Response

Not applicable.

Storage

Not applicable.

Disposal

Not applicable.

Hazardous substances

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)

▼ **Additional labelling**

EUH208, Contains 1,2-Benzisothiazol-3(2H)-one, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210, Safety data sheet available on request.

The product contains a biocidal product.

Waste disposal:

Paint and cleaning fluid must not be disposed of in drains, but collected and disposed of as environmental waste.

VOC

VOC content: < 35 g/L

MAXIMUM VOC CONTENT (Phase II, category A/d (WB): 130 g/L)

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Titanium dioxide	CAS No.: 13463-67-7 EC No.: 236-675-5 UK-REACH: Index No.:	15-25%		
2-(2-Butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	1-3%	Eye Irrit. 2, H319	[1], [3]
2-Butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 UK-REACH: Index No.: 603-014-00-0	<0.1%	Acute Tox. 4, H302 (ATE: 1200.00 mg/kg) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 3, H331	[1]
1,2-Benzisothiazol-3(2H)-one	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.036%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.036 %) Eye Dam. 1, H318 Acute Tox. 2, H330 (ATE: 0.21 mg/L)	

Aquatic Acute 1, H400 (M=10)
Aquatic Chronic 1, H410 (M=1)

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: UK-REACH: Index No.: 613-167-00-5	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
--	--	----------	---

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

In case of discomfort: bring the person into fresh air.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Rinse gently with lukewarm water. Remove any contact lenses if this is easy to do. Continue rinsing. In case of persistent eye irritation or discomfort: Seek medical help.

Ingestion

Rinse and flush mouth thoroughly and consume large quantities of water. In case of continued discomfort: seek medical assistance and bring this safety data sheet.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Some metal oxides

5.3. Advice for firefighters

No specific requirements.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

No special conditions required.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

No specific requirements.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

2-(2-Butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67,5

Short term exposure limit (15 minutes) (ppm): 15
 Short term exposure limit (15 minutes) (mg/m³): 101,2

2-Butoxyethanol

Long term exposure limit (8 hours) (ppm): 25
 Long term exposure limit (8 hours) (mg/m³): 123
 Short term exposure limit (15 minutes) (ppm): 50
 Short term exposure limit (15 minutes) (mg/m³): 246

Annotations:

BMVG = Biological Monitoring Guidance Value exists
 Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ **DNEL**

2-(2-Butoxyethoxy)ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	50 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	83 mg/kg bw/day
Long term – Local effects - General population	Inhalation	40.5 mg/m ³
Long term – Local effects - Workers	Inhalation	67.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	40.5 mg/m ³
Long term – Systemic effects - Workers	Inhalation	67.5 mg/m ³
Short term – Local effects - General population	Inhalation	60.7 mg/m ³
Short term – Local effects - Workers	Inhalation	101.2 mg/m ³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day

2-Butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	75 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	125 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	89 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	89 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	59 mg/m ³
Long term – Systemic effects - Workers	Inhalation	98 mg/m ³
Short term – Local effects - General population	Inhalation	147 mg/m ³
Short term – Local effects - Workers	Inhalation	246 mg/m ³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

Sodium benzoate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	31.25 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	62.5 mg/kg bw/day
Long term – Local effects - General population	Inhalation	0.06 mg/m ³

Long term – Local effects - Workers	Inhalation	0.1 mg/m ³
Long term – Systemic effects - General population	Inhalation	1.5 mg/m ³
Long term – Systemic effects - Workers	Inhalation	3 mg/m ³
Long term – Systemic effects - General population	Oral	16.6 mg/kg bw/day

Titanium dioxide

Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	10 mg/m ³
Long term – Systemic effects - General population	Oral	700 mg/kg bw/day

▼ PNEC

2-(2-Butoxyethoxy)ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	1,1 mg/L
Intermittent release	Continuous	11 mg/L
Marine water	Single	0.11 mg/L
Soil	Single	0.32 mg/kg soil dw

2-Butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	8.8 mg/L
Intermittent release	Continuous	26.4 mg/L
Marine water	Single	0.88 mg/L
Soil	Single	2.33 mg/kg soil dw

Sodium benzoate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.13 mg/L
Intermittent release	Continuous	305 µg/L
Marine water	Single	0.013 mg/L
Soil	Single	0.06 mg/kg soil dw

Titanium dioxide

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	184 µg/L
Intermittent release	Continuous	193 µg/L
Marine water	Single	18.4 µg/L
Soil	Single	100 mg/kg soil dw

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Wash hands after use.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment


No specific requirements.

Skin protection

No specific requirements.

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 480	EN374-2, EN16523-1, EN388



Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Various colours

Odour / Odour threshold

No data available.

pH

7 - 9

Density (g/cm³)

1,2 - 1,3

Kinematic viscosity

No data available.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

No data available.

Vapour pressure

No data available.

Relative vapour density

No data available.

Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

No data available.

Flammability (°C)

No data available.

Auto-ignition temperature (°C)

No data available.

Lower and upper explosion limit (% v/v)

No data available.

Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient (LogKow)

No data available.

Solubility in fat (g/L)

No data available.

9.2. Other information

VOC (g/L)

< 35

Other physical and chemical parameters

No data available.

Oxidizing properties

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	Titanium dioxide
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5000 mg/kg bw

Product/substance	Titanium dioxide
Species:	Rat
Route of exposure:	Inhalation

Test: LC50
Result: 3.43 - 6.82 (4 h) mg/L

Product/substance 2-(2-Butoxyethoxy)ethanol
Species: Mouse
Route of exposure: Oral
Test: LD50
Result: 2410 mg/kg bw

Product/substance 2-(2-Butoxyethoxy)ethanol
Species: Rabbit
Route of exposure: Dermal
Test: LC50
Result: 2764 mg/kg bw

Product/substance 2-Butoxyethanol
Species: Guinea pig
Route of exposure: Oral
Test: LD50
Result: 1414 mg/kg bw

Product/substance Sodium benzoate
Species: Rat
Route of exposure: Inhalation
Test: LC50 (4 hours)
Result: 12200 mg/m³

Product/substance Sodium benzoate
Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: > 2000 mg/kg bw

Based on available data for the mixture, the classification criteria are not met.

Skin corrosion/irritation

Based on available data for the mixture, the classification criteria are not met.

Serious eye damage/irritation

Based on available data for the mixture, the classification criteria are not met.

Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

Based on available data for the mixture, the classification criteria are not met.

STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

Titanium dioxide has been classified by IARC as a group 2B carcinogen.

2-Butoxyethanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	Titanium dioxide
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	155 - 294 mg/L

Product/substance	Titanium dioxide
Species:	Daphnia
Duration:	48 hours
Test:	LC50
Result:	500 mg/L

Product/substance	Titanium dioxide
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	100 mg/L

Product/substance	2-(2-Butoxyethoxy)ethanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	1300 mg/L

Product/substance	2-(2-Butoxyethoxy)ethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	> 100 mg/L

Product/substance	2-(2-Butoxyethoxy)ethanol
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	> 100 mg/L

Product/substance	2-Butoxyethanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	1474 mg/L

Product/substance	2-Butoxyethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1 550 mg/L

Product/substance	2-Butoxyethanol
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	911 mg/L

Product/substance	Sodium benzoate
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	484 mg/L

Product/substance	Sodium benzoate
Species:	Daphnia
Duration:	96 hours
Test:	LC50
Result:	> 100 mg/L

Product/substance	Sodium benzoate
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	> 30.5 mg/L

Based on available data for the mixture, the classification criteria are not met.

12.2. ▼ Persistence and degradability

Product/substance	2-(2-Butoxyethoxy)ethanol
Result:	85 %
Conclusion:	Readily biodegradable
Test:	OECD 301 C

Product/substance	2-Butoxyethanol
Result:	90,4 %
Conclusion:	Readily biodegradable
Test:	OECD 301 B

Product/substance	Sodium benzoate
Conclusion:	Readily biodegradable

12.3. ▼ Bioaccumulative potential

Product/substance	2-(2-Butoxyethoxy)ethanol
LogKow:	1,0000
Conclusion:	No potential for bioaccumulation

Product/substance	2-Butoxyethanol
LogKow:	0,8100
Conclusion:	No potential for bioaccumulation

Product/substance	Sodium benzoate
LogKow:	1,8800
Conclusion:	No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

REACH, Annex XVII

2-(2-Butoxyethoxy)ethanol is subject to restrictions, UK-REACH annex XVII (entry 55).

Additional information

Not applicable.

Sources

In accordance with Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products as retained and amended in UK law.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

EUH071, Corrosive to the respiratory tract.
H301, Toxic if swallowed.
H302, Harmful if swallowed.
H310, Fatal in contact with skin.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H330, Fatal if inhaled.
H331, Toxic if inhaled.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

DH

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en