

## TECHNICAL DATA SHEET

# NowoFacade Coating

**Product description**

NowoFacade Coating is a water-based topcoat that offers excellent UV resistance. The product is formulated with high-quality silicone binders, specialised colour pigments and micronised marble. It is mixed in a ratio that ensures the surface and paint film are highly permeable to vapour and moisture from inside, while effectively sealing out water and moisture from outside. Prevents cracks and frost damage. The paint maintains its integrity even in cities and industrial areas with high levels of air pollution, including acid gases like sulfur dioxide. The silicone binder provides protection against degradation, and its UV resistance safeguards colour pigments and other components from the sun's rays. NowoFacade Coating boasts an exceptionally long lifespan, with durability of up to 20 years. Even after many years, the surface will continue to look neat and well-maintained.

**Application**

NowoFacade Coating can be applied directly to surfaces without the need for priming or pre-treatment, except for a light dilution with water during the initial application.

Suitable for use as a topcoat over NowoFacade Primer. Surfaces must be clean and dry prior to application. Glass or plastic windows should be properly covered during treatment.

**Highlights & Features**

- UV and weather resistant
- Strong water-repellent properties
- Highly flexible paint film with excellent flow properties
- Permeable
- Excellent coverage
- Less spray dust

**Recommendation**

Important! Always do a test swipe on a small test area to ensure compatibility of the product and the surface being treated.



COATING THE FUTURE



**Technical data**

<b>Colour:</b>	Can be tinted on request
<b>Drying time:</b>	At 20°C and 65% relative humidity, approximately 1 hour, depending on the thickness of layer applied
<b>Coverage capacity:</b>	4-6m <sup>2</sup> per litre depending on the application method and layer thickness
<b>Application:</b>	Brush, roller or spray gun (nozzle size 0.018 -0.026")
<b>Dilution:</b>	The product must be used undiluted
<b>Cleaning:</b>	Soap and water
<b>Gloss:</b>	Matt
<b>Recoating Time:</b>	After approx. 2 hours (at 20°C / 65% RH), you can repaint within a maximum of 24 hours
<b>Packaging:</b>	10 ltr. bucket
<b>Storage:</b>	Dry, frost-free and inaccessible to children
<b>Disposal:</b>	Dispose of contents/container in accordance with local waste regulations

Download the latest safety data sheet at [www.nowocoat.com](http://www.nowocoat.com) for more information

*This Technical Data Sheet (TDS) has been compiled on the basis of our many years of experience and latest know-how in the field. It is the intention to support craftsmen in choosing the right materials and using them according to the regulations. The information contained in this TDS does not constitute a guarantee and does not exempt users from the responsibility to check the material and its suitability for the intended use. All new versions replace previous TDS versions. Last updated 10.10.2024*

COATING THE FUTURE

