

SAFETY DATA SHEET

140820-001 - NowoProtect - S-40

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

140820-001 - NowoProtect - S-40

Unique formula identifier (UFI)

NWY8-YMAH-AWS2-KK0M

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼ Relevant identified uses of the substance or mixture

Impregnation of mineral surfaces

Restricted to professional and industrial use.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

NOWOCOAT INDUSTRIAL A/S

Stålvvej 3

6000 Kolding

Denmark

Tel: +45 7550 1111

E-mail

mail@nowocoat.dk

Revision

14/04/2026

SDS Version

5.0

Date of previous version

30/09/2025 (4.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 111 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. ▼ Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

▼ **Hazard statement(s)**

- Flammable liquid and vapour. (H226)
- Causes skin irritation. (H315)
- Causes serious eye irritation. (H319)

Precautionary statement(s)

General

Not applicable.

▼ **Prevention**

- Wash hands thoroughly after handling. (P264)
- Wear protective gloves/protective clothing/eye protection/face protection. (P280)

▼ **Response**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
- If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal

Dispose of contents/container in accordance with local regulation. (P501)

▼ **Hazardous substances**

Contains no substances that need to be listed on the label.

Additional labelling

UFI: Nwy8-YMAH-AWS2-KK0M

Waste disposal:

Paint and cleaning fluid must not be disposed of in drains, but collected and disposed of as environmental waste.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH: Index No.: 603-002-00-5	40-60%	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
Triethoxyisobutylsilane	CAS No.: 17980-47-1 EC No.: 402-810-3 UK-REACH: 01-0000015254-76-xxxx Index No.: 014-007-00-1	40-60%	Skin Irrit. 2, H315	

Propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	10-15%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
-------------	---	--------	---

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

▼ Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. ▼ Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap.

Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

No specific requirements.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol

Long term exposure limit (8 hours) (ppm): 1000

Long term exposure limit (8 hours) (mg/m³): 1920

Propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m ³
Long term – Systemic effects - Workers	Inhalation	950 mg/m ³
Short term – Local effects - General population	Inhalation	950 mg/m ³
Short term – Local effects - Workers	Inhalation	1900 mg/m ³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

Propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day

PNEC

Ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	960 µg/L
Intermittent release	Continuous	2,75 mg/L
Marine water	Single	790 µg/L
Soil	Single	630 µg/kg soil dw

Propan-2-ol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	140,9 mg/L
Intermittent release	Continuous	140.9 mg/L
Marine water	Single	140,9 mg/L
Soil	Single	28 mg/kg soil dw

Triethoxyisobutylsilane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.17 mg/L
Intermittent release	Single	1.7 mg/L
Marine water	Single	0.017 mg/L
Soil	Single	2.7 mg/kg soil dw

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

▼ Respiratory Equipment

Type	Class	Colour	Standards
Combination filter A2P2	Class 2	Brown/White	EN14387



Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Neoprene (Neoprene)	0,6	> 480	EN374-2, EN16523-1, EN388



Eye protection

Type	Standards
Safety glasses	EN ISO 16321-1



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

No data available.

Odour / Odour threshold

Solvent

pH

Not applicable - water solubility < 1 mg/L @ 20°C

Density (g/cm³)

0,80 - 0,84

Kinematic viscosity

No data available.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

No data available.

Vapour pressure

No data available.

Relative vapour density

No data available.

Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

>23

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

No data available.

Lower and upper explosion limit (% v/v)

No data available.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient (LogKow)

No data available.

Solubility in fat (g/L)

No data available.

9.2. Other information

VOC (g/L)

<830

Other physical and chemical parameters

No data available.

Oxidizing properties

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	Ethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	1187 - 15010 mg/kg bw ·

Product/substance	Ethanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	115.9 - 133.8 mg/L air (4 h) ·

Product/substance	Triethoxyisobutylsilane
Species:	Rat

Route of exposure: Oral
 Test: LD50
 Result: > 5000 mg/kg bw ·

Product/substance Triethoxyisobutylsilane
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: > 5.88 mg/L air (4 h) ·

Product/substance Triethoxyisobutylsilane
 Species: Rat
 Route of exposure: Dermal
 Test: LD50
 Result: > 2000 mg/kg bw ·

Product/substance Propan-2-ol
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: 5840 mg/kg bw

Product/substance Propan-2-ol
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: 10000 (6 h) ppm

Product/substance Propan-2-ol
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: 16.4 mL/kg bw ·

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

▼ **Serious eye damage/irritation**

Causes serious eye irritation.

▼ **Respiratory sensitisation**

Based on available data, the classification criteria are not met.

▼ **Skin sensitisation**

Based on available data, the classification criteria are not met.

▼ **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

▼ **Carcinogenicity**

Based on available data, the classification criteria are not met.

▼ **Reproductive toxicity**

Based on available data, the classification criteria are not met.

▼ **STOT-single exposure**

Based on available data, the classification criteria are not met.

▼ **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

▼ **Aspiration hazard**

Based on available data, the classification criteria are not met.

▼ **Symptoms related to the physical, chemical and toxicological characteristics**

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
 Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

11.2. Information on other hazards

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

Propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	Ethanol
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	14.2 - 15.4 g/L ·

Product/substance	Ethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	10 g/L ·

Product/substance	Ethanol
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	275 mg/L ·

Product/substance	Triethoxyisobutylsilane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	85 mg/L ·

Product/substance	Triethoxyisobutylsilane
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	> 49.1 mg/L ·

Product/substance	Triethoxyisobutylsilane
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	> 100 mg/L ·

Product/substance	Propan-2-ol
Species:	Fish
Duration:	96 hours
Test:	LC50

Result: 9.64 - 10 g/L

Product/substance Propan-2-ol
 Species: Daphnia
 Duration: 24 hours
 Test: EC50
 Result: > 10 g/L

Based on available data, the classification criteria are not met.

12.2. ▼ Persistence and degradability

Product/substance Ethanol
 Result: 74 %
 Conclusion: -
 Test: OECD 301 A

Product/substance Propan-2-ol
 Result: 90-100 %
 Conclusion: -

12.3. ▼ Bioaccumulative potential

Product/substance Ethanol
 LogKow: -0,3500
 Conclusion: -

Product/substance Propan-2-ol
 LogKow: 0,0500
 Conclusion: -

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.




EWC code

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/A DN/RID	UN1987	ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1987	ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-D See below for additional information.
IATA	UN1987	ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol)	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

REACH, Annex XVII

Ethanol is subject to UK-REACH restrictions (entry 40).

Propan-2-ol is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EC = Effective concentration

ED = Effective dose

EINECS = European Inventory of Existing Commercial chemical Substances

EL = Effective Loading

ErC = Concentration associated with x% growth rate response

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWG = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

HP = Hazardous Property code

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IC = X maximum inhibitory concentration

IMDG = International Maritime Dangerous Goods

LC = Lethal concentration

LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans

LD = Lethal dose

LOAEC = Lowest Observed Adverse Effect Concentration

LOAEL = Lowest Observed Adverse Effect Level

LOEC = Lowest Observed Effect Concentration

LogKow = logarithm of the n-octanol/water coefficient

LL = Lethal Loading

M = For multiplication factor

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NOAEC = No Observed Adverse Effect Concentration
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
NOELR = No Observable Effect Loading Rate
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

DH

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en