

TECHNICAL DATA SHEET

NowoProtect Seal SB

Product description

NowoProtect Seal SB is a solvent based impregnation based on the very latest nanotechnology that penetrates into even hard surfaces such as granite and marble, but can also be used for all mineral surfaces where protection against water, oil, grease from the grill, ketchup, red wine, etc. is required. Also protects against dirt and algae.

NowoProtect Seal SB has self-cleaning properties that minimize adhesion of stains, green coatings and oil stains. The treated surface does not form a film, is full diffusion open and colorless after completion of treatment.

Application

For newer surfaces less than 1 year old, keep in mind that they are dry and free from impurities before impregnation. Surfaces older than 1 year must be thoroughly cleaned with a high pressure cleaner and finally disinfected with NowoClean Mineral Cleaner. Hereby you get a deep cleaning that removes the dirt before sealing it with NowoProtect Seal SB. The surface must be clean and dry before applying NowoProtect Seal SB.

Highlights & Features

- Stain repellent
- Dirt repellent
- Grease repellent
- Oil repellent
- Water repellent
- UV resistant
- Colorless
- Diffusion open
- Inhibits the development of algae and other green coatings and prevents frost damage.

Surfaces treated with NowoProtect Seal SB are easier to maintain and clean.

Recommendation

Always test a small area to ensure product compatibility with the surface. If NowoProtect Seal SB splashes onto the windows or glass of any kind, it must be wiped away from windows immediately.



COATING THE FUTURE



Technical data

Color:	Colorless
Drying Time:	Approx. 1-2 hours at 20 degrees (60% relative humidity). Can be walked on after approx. 6 hours, traffic only after a minimum of 24 hours, hardened after 6-8 days at 20 degrees.
Range:	Approx. 2-12 m ² / liter depending on absorbency.
Application:	Brush, paint roller or low pressure sprayer.
Dilution:	Ready to use, do not dilute.
Cleaning:	Cleaned in turpentine immediately after use.
Packaging:	25 Liter
Shelf life:	24 months in original unbroken packaging
Storage:	Dry, frost free and out of reach of children.

Download the latest safety data sheet at www.nowocoat.com for more information

This Technical Data Sheet (TDS) has been compiled on the basis of our many years of experience and latest know-how in the field. It is the intention to support craftsmen in choosing the right materials and using them according to the regulations. The information contained in this TDS does not constitute a guarantee and does not exempt users from the responsibility to check the material and its suitability for the intended use. All new versions replace previous TDS versions. Last updated 01.10.2024

COATING THE FUTURE

